

9710  
County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

T26S	R2E
S18	S17
S19	S20

1929

from which,

A pine, 20 ins. diam., bears N.17°E., 79 lks. dist.,  
mkd. T 26 S R 2 E S 17 B T

A fir, 40 ins. diam., bears S.1½°E., 119 lks. dist.,  
mkd. T 26 S R 2 E S 20 B T

A fir, 42 ins. diam., bears S.9°W., 151 lks. dist.,  
mkd. T 26 S R 2 E S 19 B T

A fir, 50 ins. diam., bears N.85°W., 236 lks. dist.,  
mkd. T 26 S R 2 E S 18 B T

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, pine, cedar, hemlock, and yew.

Undergrowth; mountain laurel, grease wood, chinquapin,  
manzanita, small fir, and arrow-wood.

- S.89°47'E., on a random line bet. secs. 17 and 20.
- 40.00 Set temp. ¼ sec. cor.
- 80.02 Intersect N. and S. line, 28 lks. S. of cor. of secs. 16, 17, 20 and 21, hereinbefore described
- Thence
- N.89°59'W., on true line bet. secs. 17 and 20
- Asc. 289 ft. over SE. slope, through heavy timber and dense undergrowth.
- 7.80 Spur, slopes S.20°E., desc. 12 ft. along broken SW. slope.
- 10.83 Intersect line bet. cors. Nos. 1 and 9, H. E. S. No. 93;  
Cor. No. 1 bears S.40°45'E., 9.09 chs. dist.,
- 21.00 Draw, course S., asc. 93 ft. over SE. slope.