

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS	
79.77	Intersect W. bdy. of Tp. 14 lks. S. of cor. of secs. 13, 18, 19, and 24, as described in the field notes of T. 26 S., R. 1 E., this Group.
	Thence
	N.89*56'E., on true line bet. secs. 18 and 19.
	Desc. 18 ft. over E. slope, through heavy timber and dense undergrowth.
0.50	Creek, 1 lk. wide, course S., asc. 113 ft. over SW. slope.
7.20	Spur, slopes SE., desc. 24 ft. over SE. slope.
8.80	Dog Creek, 4 lks. wide, course S.10*W., asc. 780 ft. over W. slope.
26.50	Spur, slopes SW., asc. 192 ft. over SW. slope.
36.00	Spur, slopes S., desc. 33 ft. over SE. slope.
36.39	Intersect line bet. cors. Nos. 2 and 3, H. E. S. No. 182; Cor. No. 2 bears S.0*49'W., 2.74 chs. dist.
39.77	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bed rock, and in mound of stone, 4 ft. base, for 1/4 sec. cor. of secs. 18 and 19, with brass cap mkd.
	$\frac{1}{4} \frac{S18}{S19}$
	1929
	from which,
	A fir, 9 ins. diam., bears N.49*E., 135 lks. dist.,
	mkd. 1/4 S 18 B T
	A fir, 4 ins. diam., bears S.61*W., 52 lks., dist.,
	mkd. 1/4 S 19 B T
	Along broken S. slope.
45.80	Desc. 116 ft. over SE. slope.
57.00	Draw, course SE., along broken S. slope.
59.00	House bears North, about 6.00 chs. dist.
71.80	Way trail, bears SE. and NW.