

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

- 68.90 Desc. 151 ft. over NW. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 29 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.

T26S	R2E
S 7	S 8
S18	S17
1930	

from which,

- A fir, 15 ins. diam., bears N.62*E., 55 lks. dist.,
mkd. T 26 S R 2 E S 8 B T
- A fir, 16 ins. diam., bears S.34*E., 66 lks. dist.,
mkd. T 26 S R 2 E S 17 B T
- A fir, 12 ins. diam., bears S.51*W., 51 lks. dist.,
mkd. T 26 S R 2 E S 18 B T
- A fir, 15 ins. diam., bears N.19*W., 56 lks. dist.,
mkd. T 26 S R 2 E S 7 B T

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, cedar, hemlock, madrona, and chinquapin,

Undergrowth; buck brush, vinemaple, and rhododendron.

S.89*59'E., on a random line bet. secs. 8 and 17.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.94 Intersect N. and S; line, 19 lks. N. of cor. of secs. 8, 9, 16 and 17, hereinbefore described.
- Thence
- N.89*51'W., on true line bet. secs. 8 and 17
- Asc. 206 ft. over E. slope, through medium timber and medium undergrowth.
- 7.50 Spur, slopes N., along broken N.slope.
- 15.80 Draw, course N.,
- 19.00 Spur, slopes N.,
- 21.20 Draw, course N., asc. 592 ft. over NE. slope.
- 39.97 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in