

County Surveyor's Record, Douglas County, Oregon

East and North Boundaries and
Subdivisional lines of
T.26 S., R. 3 E.,

Executed by Otto L. Draper, U.S. Transitman, under Special
Instructions, dated Dec. 27, 1920.

CHAINS

East Boundary of T. 26 S., R. 3 E.

From the cor. of Tps. 26 and 27 S., Rs. 3 and 4 E.,
which is an iron post, 3 ins. diam., 8 ins. above
ground, marked and witnessed as described in the
official record.

North bet. secs. 31 and 36, on E. bdy. of Tp.


Asc. 470 ft. over broken SE. slope, through heavy
timber and dense undergrowth.

12.40 Top of bluff, rimrock, bears N.80°E. and S.80°W.,

15.00 Top of ascent, bears E. and W., thence over nearly
level bench

24.00 Through heavy open timber.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which


A cedar, 34 ins. in diam., bears N.36°E., 31 lks.
dist. mkd. $\frac{1}{4}$ S 31 B T

A fir, 12 ins. in diam., bears S.74°W., 55 lks.,
dist. mkd. $\frac{1}{4}$ S 36 B T.

71.80 Top of descent bears NE. and SW., desc. ~~327~~ ft. over
broken N.W. slope through heavy timber and medium
undergrowth.

75.10 Top of bluff, rimrock, bears NE. and SW., 60 ft. high,
descent becomes steep.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in
the ground, to bed rock, and in a mound of stone to
top, for cor. of secs. 25, 30, 31 and 36, with brass
cap mkd.



from which