

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 26 S., R. 3 E.

CHAINS													
47.00	Draw, course NE., along broken E. slope.												
57.10	Draw, course SE.,												
64.10	Small stream, course NE.												
69.90	Head of draw, course SE., asc. 130 ft. over S. slope.												
73.40	Ridge, bears E. and W., desc. 48 ft. along broken NE.												
	slope.												
80.00	Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in												
	the ground, for cor. of Tps. 25 $\frac{1}{2}$ and 26 S., Rs. 3												
	and 4 E., with brass cap mkd.												
	<table border="0"> <tr><td colspan="2">T25$\frac{1}{2}$S</td></tr> <tr><td>R3E</td><td>R4E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td>S1</td><td>S6</td></tr> <tr><td colspan="2">T26S</td></tr> <tr><td colspan="2">1930</td></tr> </table>	T25 $\frac{1}{2}$ S		R3E	R4E	S36	S31	S1	S6	T26S		1930	
T25 $\frac{1}{2}$ S													
R3E	R4E												
S36	S31												
S1	S6												
T26S													
1930													
	from which												
	A fir, 72 ins. diam., bears N.50*E., 94 lks.												
	dist., mkd. T 25 $\frac{1}{2}$ S R 4 E S 31 B T												
	A fir, 44 ins. diam., bears S.74*E., 40 lks.												
	dist., mkd. T 26 S R 4 E S 6 B T												
	A fir, 22 ins. diam., bears S.57*W., 85 lks.												
	dist., mkd. T 26 S R 3 E S 1 B T												
	A fir, 22 ins. diam., bears N.79*W., 108 lks.												
	dist., mkd. T 25 $\frac{1}{2}$ S R 3 E S 36 B T												