


Subdivisions of T. 26 S., R. 3 E.

CHAINS

Asc. 430 ft. over broken SW. slope, through heavy timber and medium undergrowth, to 1/4 sec. cor.

8.20 Spur, slopes SW.,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



from which

A fir, 18 ins. diam., bears N.38*E., 29 lks. dist., mkd. 1/4 S 13 B T.


A fir, 14 ins. diam., bears N.46*W., 8 lks. dist., mkd. 1/4 S 14 B T.

Asc. 250 ft. over SW. slope.

60.30 Ridge, bears E. and W., desc. 160 ft. over NW. slope.

77.90 Head of draw, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 11, 12, 13, and 14, with brass cap mkd.



from which

A cedar, 26 ins. diam., bears N.40*E., 123 lks. dist., mkd. T 26 S R 3 E S 12 B T

A fir, 28 ins. diam., bears S.59*E., 127 lks. dist., mkd. T 26 S R 3 E S 13 B T

A fir, 26 ins. diam., bears S.58*W., 16 lks. dist., mkd. T 26 S R 3 E S 14 B T

A fir, 36 ins. diam., bears N.14*W., 10 lks. dist., mkd. T 26 S R 3 E S 11 B T

Land; mountainous.

Soil; volcanic ash, 4th rate.