

Subdivisions of T. 26 S., R. 3 E.

CHAINS

N.0*02'W., bet. secs. 26 and 27.

Desc. 178 ft. over NE. slope, through heavy timber and medium undergrowth.

8.70 Draw, course NW., along W. slope.


16.20 Desc. 121 ft. over NW. slope.

22.20 Draw, course W., asc. 157 ft. over SW. slope.

33.60 Spur, slopes W., desc. 206 ft. over NW. slope.

38.80 Small stream, course NW., asc. 26 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the 1/4 sec. cor., with brass cap mkd.



from which

A fir, 40 ins. diam., bears East, 37 lks. dist., mkd. 1/4 S 26 B T

A fir, 12 ins. diam., bears S.85*W., 89 lks. dist., mkd. 1/4 S 27 B T

Asc. 235 ft. over SW. slope.

48.70 Spur, slopes W., desc, 63 ft. over NW. slope.


50.80 Draw, course SW., asc. 374 ft. over SW. slope.

62.50 Spur, slopes SW., desc, 50 ft. over NW. slope.

69.10 Draw, course SW., asc. 205 ft. over SE. slope.

76.10 Spur, slopes SW., desc, 95 ft. over NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins in the ground, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.



from which

A fir, 22 ins. diam., bears N.12*E., 34 lks. dist., mkd. T 26 S R 3 E S 23 B T

A fir, 28 ins. diam., bears S.57*E., 44 lks.