

County Surveyor's Record, Douglas County, Oregon

393


Subdivisions of T. 26 S., R. 3 E.,

CHAINS

N.0*02'W., bet. secs. 10 and 11

Asc. 560 ft. over S., changing to SE. slope, through heavy timber and dense undergrowth.

- 5.10 Top of bluff, facing SW.,
- 20.40 Ridge, "Camels Hump", bears SW. and N., along top.
- 25.50 Ridge, bears N.5*E., desc. 150 ft. over NW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which,

A fir, 11 ins. diam., bears S.32*E., 28 ins.

dist., mkd. $\frac{1}{4}$ S 11 B T

A fir, 9 ins. diam., bears N.57*W., 28 ins.


dist., mkd. $\frac{1}{4}$ S 10 B T

- 41.70 Ridge, bears NW. and S.30*E., desc. 426 ft. over NE. slope.

- 58.60 Draw, course SE., asc. 70 ft. along broken E. slope, to cor.

- 74.00 Draw, course SE.,

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.



from which

A fir, 35 ins. diam., bears N.25*E., 45 lks.

dist., mkd. T 26 S R 3 E S 2 B T

A fir, 22 ins. diam., bears S.19*E., 101 lks.

dist., mkd. T 26 S R 3 E S 11 B T

A pine, 32 ins. diam., bears S.42*W., 37 lks.

dist., mkd. T 26 S R 3 E S 10 B T