

Subdivisions of T. 26 S., R. 3 E.

CHAINS	<p>A fir, 18 ins. diam., bears S.12*W., 62 lks. dist., mkd. T 26 S R 3 E S 33 B T</p> <p>A cedar, 6 ins. diam., bears N.67*W., 62 lks. dist., mkd. T 26 S R 3 E S 28 B T</p> <p>Land; nearly level bench.</p> <p>Soil; mountain loam, 3rd rate.</p> <p>Timber; fir, cedar, hemlock, pine, yew, dog wood, and chinquapin.</p> <p>Undergrowth; willow, chinquapin, vinemaple, rhododendron, and young fir.</p>
	<p>East on a random line bet. secs. 27 and 34.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.80	Intersect N. and S. line, 42 lks. N. of cor. of secs. 26, 27, 34 and 35.
	Thence
	N.89*42*W., on true line bet. secs. 27 and 34.
	Along broken N. slope, through heavy timber and dense undergrowth.
7.00	Desc. 90 ft. over NW. slope.
10.00	Top of bluff, 70 ft. high, facing W., desc., 890 ft. over W., changing to NW. slope.
31.20	Right bank of North Umpqua River, course N.20*W.,
32.40	Left bank of river, asc. 673 ft. over E., changing to NE. slope, over bluffs.
39.90	True point for $\frac{1}{4}$ sec. cor. falls on steep insecure ground
49.70	Top of bluff, 90 ft. high, facing NE.,
49.82	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to bedrock, and in mound of stone, to top, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	WC $\frac{1}{4}$ $\frac{S27}{S34}$ 1930
	from which