

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 E.

CHAINS	
	<p>A fir, 26 ins. diam., bears N.84*W., 192 lks. dist., mkd. W C $\frac{1}{4}$ S 27 B T</p> <p>A fir, 18 ins. diam., bears S.61*W., 186 lks. dist., mkd. W C $\frac{1}{4}$ S 34 B T</p> <p>Asc. 263 ft. over NE. slope, over bluffs.</p>
56.00	Top of ascent, bears NW. and SE., over nearly level bench.
79.80	The cor. of secs. 27, 28, 33 and 34.
	<p>Land; mountainous.</p> <p>Soil; rocky, 4th rate.</p> <p>Timber; fir, hemlock, pine, and yew.</p> <p>Undergrowth; rhododendron, vinemapple, hazel and young fir.</p>
	<p>N.0*02*W., bet. secs. 27 and 28.</p> <p>Over nearly level bench, through heavy timber and medium undergrowth.</p>
13.00	Top of descent, bears NW. and SE., desc. 986 ft. over NE. slope.
36.15	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<p style="text-align: center;">W C $\frac{1}{4}$ S28 S27 1930</p> <p style="text-align: right;">from which</p>
	<p>A hemlock, 16 ins. diam., bears S.46*E., 28 lks. dist., mkd. W C $\frac{1}{4}$ S 27 B T</p> <p>A cedar, 28 ins. diam., bears N.64*W., 22 lks. dist., mkd. W C $\frac{1}{4}$ S 28 B T</p>
	Desc. 121 ft. over NE. slope.
39.80	Left bank of North Umpqua River, course W.,
40.00	True point for $\frac{1}{4}$ sec. cor., falls in river.
40.60	Right bank of river, bluff, 50 ft. high, bears E. and W., asc. 1124 ft. over broken SW. slope.