

Subdivisions of T. 26 S., R. 3 E.

CHAINS

58.50 Top of bluff, 123 ft. high, facing SW.,  
 60.10 Draw, course SW.,  
 75.70 Spur, slopes SW., desc. 125 ft. over NW. slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
 the ground, for cor. of secs. 21, 22, 27 and 28, with  
 brass cap mkd.

T26S	R3E
S21	S22
S28	S27

1930

from which

A fir, 7 ins. diam., bears N.31\*E., 28 lks.

dist., mkd. T 26 S R 3 E S 22 B T

A fir, 32 ins. diam., bears S.23\*E., 109 lks.

dist., mkd. T 26 S R 3 E S 27 B T

A fir, 14 ins. diam., bears S.69\*W., 43 lks.

dist., T 26 S R 3 E S 28 B T

A fir, 9 ins. diam., bears N.63\*W., 58 lks.

dist., mkd. T 26 S R 3 E S 21 B T

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, cedar, pine, chinquapin, madrona and hemlock.

Undergrowth; rhododendron, chinquapin, manzanita, and  
 vinemaple.

S.89\*42'E., on a random line bet. secs. 22 and 27

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.60 Intersect N. and S. line, 11 lks. S. of cor. of secs.  
 22, 23, 26 and 27.

Thence

N.89\*47'W., on true line bet. secs. 22 and 27

Desc. 18 ft. over NW. slope, through heavy timber and dense  
 undergrowth.

0.80 Draw, course SW., desc. 56 ft. over SW. slope.