

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 E.

CHAINS


N.0*02'W., bet. secs. 21 and 22.

Desc. 226 ft. over NW. slope, through heavy timber and medium undergrowth;

8.30 Creek, 1 lk. wide, course W., asc. 412 ft. over SE. slope.

33.00 Ridge spur, bears NE. and SW., desc. 47 ft. over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the 1/4 sec. cor., with brass cap mkd.



from which

A fir, 44 ins. diam., bears N.27*E., 56 lks. dist., mkd. 1/4 S. 22 B T

A fir, 49 ins. diam., bears S.83*W., 69 lks. dist., mkd. 1/4 S 21 B T

Desc. 650 ft. over broken NW. slope to Slide Creek.

66.50 Draw, course NW.,

67.70 Top of bluff, facing N.,

70.60 Small spur, slopes NW.,

76.10 Draw, course NW.,

79.70 Slide Creek, 5 lks. wide, course SW., asc. 35 ft. over SE. slope, bare rock.

80.00 The true point for cor. of secs. 15, 16, 21 and 22, falls on steep bare rock;

Thence

S.89*51'E., 2.98 chs.

A fir, 36 ins. diam., for witness cor. of secs. 15, 16, 21, and 22, mkd.

T 26 S S 15 on NE.,

R 3 E S 22 on SE.,

W C S 21 on SW., and

S 16 on NW., sides,

from which,