

County Surveyor's Record, Douglas County, Oregon

9787  
53

Subdivisions of T. 26 S., R. 8 E.

CHAINS	
	N.89*59'E., on a random line bet. secs. 3 and 10.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.36	Intersect N. and S. line, 14 lks. S. of cor. of secs. 2, 3, 10 and 11.
	Thence
	S.89*53'W., on true line bet. secs. 3 and 10.
	Asc. 216 ft. over SE. slope, through heavy timber and dense undergrowth.
27.70	Spur, slopes SE., desc. 65 ft. along SW. slope.
40.18	A fir, 42 ins. diam., for the $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ S 3 on N., and S 10 on S., side.
	from which
	A fir, 16 ins. diam., bears S.30*W., 51 lks. dist., mkd. $\frac{1}{4}$ S 10 B T
	A cedar, 16 ins. diam., bears N.52*W., 20 lks. dist., mkd. $\frac{1}{4}$ S 3 B T
	Desc. 616 ft. over W., changing to SW. slope.
49.10	Top of bluff, 20 ft. high, facing W.
60.20	Draw, course S., asc. 22 ft. over SE. slope.
65.80	Low saddle in ridge, bears N. and S., asc. 331 ft. over E., changing to NE. slope.
70.90	Way trail, bears N. and S.,
80.36	Cor. of secs. 3, 4, 9 and 10.
	Land; mountainous.
	Soil; rocky, 4th rate.
	Timber; fir, cedar, hemlock, pine and yew.
	Undergrowth; rhododendron, vinemaple and young fir.
	<hr/>
	N.0*02'W., on a random line bet. secs. 3 and 4.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.98	Intersect N. bdy. of Tp. 15 lks. W. of cor. of secs. 3, 4, 33 and 34.