

Subdivisions of T. 26 S., R. 3 E.

CHAINS

N.0\*03'W., bet.secs. 32 and 33.

Desc. 660 ft. over broken NE. slope, to the  $\frac{1}{4}$  sec. cor. through heavy timber and medium undergrowth.

7.30 North Umpqua Trail and forest service telephone line, bears NW. and SE.


18.90 Small stream, course NE.,

27.80 Spur, slopes NE.,

32.20 Small stream, course NE.

35.10 Draw, course NE.,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A hemlock, 14 ins. diam., bears N.88\*E., 11 lks. dist., mkd.  $\frac{1}{4}$  S.33 B T

A fir, 32 ins. diam., bears S.71\*W., 24 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T

Asc. 52 ft. over SE. slope.

49.50 Spur, slopes NE., desc. 191 ft. over broken NE. slope.


56.60 Draw, course E., asc. 65 ft. over SE.

61.50 Spur, slopes N.70\*E., desc. 200 ft. over NE. slope.

64.80 Draw, course E., asc. 313 ft. over broken SE. slope, to cor.

73.60 Draw, course SE.,

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, to bedrock, and in mound of stone to top, for, cor. of secs. 28,29, 32 and 33, with brass cap mkd.



from which