

## Subdivisions of T. 26 S., R. 3 E.

CHAINS	
80.00	<p>A fir, 10 ins. diam., for the cor. of secs. 20, 21, 28 and 29, mkd.</p> <p>T 26 S S 21 on NE.,  R 3 E S 28 on SE.,  S 29 on SW., and  S 20 on NW., side.</p> <p style="text-align: right;">from which,</p> <p>A fir, 12 ins. diam., bears N.79°E., 92 lks. dist., mkd. T 26 S R 3 E S 21 B T</p> <p>A cedar, 34 ins. diam., bears S.72°E., 67 lks. dist., mkd. T 26 S R 3 E S 28 B T</p> <p>A fir, 14 ins. diam., bears S.59°W., 60 lks. dist., mkd. T 26 S R 3 E S 29 B T</p> <p>A fir, 8 ins. diam., bears N.56°W., 25 lks. dist., mkd. T 26 S R 3 E S 20 B T</p> <p>Land; mountainous.</p> <p>Soil; rocky, 4th rate.</p> <p>Timber; fir, cedar, hemlock, and madrona.</p> <p>Undergrowth; vinemaple, rhododendron, and dog wood.</p>
40.00	<hr/> <p>S.89°43'E., on a random line bet. secs. 21 and 28</p> <p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p>
79.96	<p>Intersect N. and S. line, 3 lks. S. of cor. of secs. 21, 22, 27 and 28.</p> <p>Thence</p> <p>N.89°44'W., on true line bet. secs. 21 and 28.</p> <p>Desc. 667 ft. over broken NW. slope, through heavy timber and medium undergrowth.</p>
19.20	<p>Top of bluff, 80 ft. high, facing NW.,</p>
22.30	<p>Draw, course SW., asc. 37 ft. over SE. slope.</p>
25.10	<p>Spur, slopes SW., desc. 284 ft. over SW. slope.</p>
39.98	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p>