


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 E.

CHAINS



from which

A fir, 30 ins. diam., bears S.28*E., 48 lks.

dist., mkd. W C $\frac{1}{4}$ S 21 B T

A fir, 26 ins. diam., bears N.26*W., 64 lks.

dist., mkd. W C $\frac{1}{4}$ S 20 B T

33.50 Top of bluff, 200 ft. high, facing NE., desc. 340 ft. over precipitous NE. slope.

40.00 The true point for cor. falls on face of bluff, 120 ft. high, facing NE., desc. 70 ft. over bluff.

41.00 Foot of bluff, bears NW. and SE., desc. 400 ft. over broken NE. slope.

61.80 Top of bluff, 85 ft. high, facing N., desc. 100 ft. over N. slope, over bluff.


62.00 Left bank of North Umpqua River, course W.,

63.50 Right bank of river, at mouth of Medicine Creek, 5 lks. wide, from N., asc. 44 ft. over S. slope, up creek,

70.70 Leave creek, from N.10*E., asc. 62 ft. over SE. slope.

77.60 Small stream, course SE., asc. 99 ft. over SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.



from which

A fir, 30 ins. diam., bears N.54*E., 90 lks.

dist., mkd. T 26 S R 3 E S 16 B T

A fir, 28 ins. diam., bears S.29*E., 20 lks.

dist., mkd. T 26 S R 3 E S 21 B T

A fir, 28 ins. diam., bears S.42*W., 118 lks.

dist., mkd. T 26 S R 3 E S 20 B T