

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 3 E.

CHAINS	<p>Land; mountainous.</p> <p>Soil; volcanic ash, 4th rate.</p> <p>Timber; fir, pine, cedar, yew and madrona.</p> <p>Undergrowth; rhododendron, arrow wood, hazel, and young fir and cedar.</p>
	<p>West, on a random line bet. secs. 30 and 31</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.08	Intersect W. bdy. of Tp. 5 lks. S. of cor. of secs. 25, 30, 31 and 36, which is an iron post, 2 ins. diam., firmly set in mound of stone, 6 ft. base, $2\frac{1}{2}$ ft. high, marked and witnessed as described in the official record.
	<p>Thence</p> <p>S.89*58'E., on true line bet. secs. 30 and 31</p> <p>Asc. 300 ft. over gradual broken W. slope, through medium timber and medium undergrowth, across "Oak Flats."</p>
13.20	North Umpqua Trail, and forest service telephone line, bears NW. and SE.
39.08	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S30}{S31}$ <p>1930</p>
	from which
	<p>A cedar, 34 ins. diam., bears N.52*E., 55 lks. dist., mkd. <math>\frac{1}{4}</math> S 30 B T</p> <p>A fir, 10 ins. diam., bears S.66*E., 47 lks. dist., mkd. <math>\frac{1}{4}</math> S 31 B T</p>
	Asc. 590 ft. over broken NW. slope.
42.00	Draw, course NW.,
44.80	Small stream, course NW.,
63.10	Spur, slopes SW., asc. 40 ft. over SW., changing to S. slope.
79.08	The cor. of secs. 29, 30, 31 and 32.