

County Surveyor's Record, Douglas County, Oregon


Subdivisions of T. 26 S., R. 3 E

CHAINS

N.0*04'W., bet. secs. 19 and 20.

Desc. 490 ft. over NE. slope, through heavy timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 36 ins. diam., bears S.73*E., 125 lks.

dist., mkd. $\frac{1}{4}$ S 20 B T

A fir, 33 ins. diam., bears S.46*W., 113 lks.

dist., mkd. $\frac{1}{2}$ S 19 B T

Over rolling bench land, through medium timber and light undergrowth.

72.30 Rim of North Umpqua River canyon, bears NW. and SE., desc. 345 ft. over NE. slope.

79.40 Draw, course NE.,

80.00 A fir, 17 ins. diam., for the cor. of secs. 17, 18, 19, and 20, mkd.

T 26 S S 17 on NE.,

R 3 E S 20 on SE.,

S 19 on SW., and

S18 on NW., side

from which

A fir, 46 ins. diam., bears N.67*E., 42 lks.

dist., mkd. T 26 S R 3 E S 17 B T

A cedar, 16 ins. diam., bears S.83*E., 41 lks.

dist., mkd. T 26 S R 3 E S 20 B T

A fir, 24 ins. diam., bears S.60*W., 40 lks.

dist., mkd. T 26 S R 3 E S 19 B T

A pine, 42 ins. diam., bears N.88*W., 64 lks.

dist., mkd. T 26 S R 3 E S 18 B T