


Subdivisions of T. 26 S., R. 3 E.

CHAINS

- 20.10 Way trail, bears E. and W.,
- 24.00 Same trail, bears SW. and NE.
- 25.00 Same trail, bears NW. and SE.,
- 33.20 Spur, slopes NW., desc. 210 ft. over N. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the 1/2 sec. cor., with brass cap mkd.



from which

A fir, 16 ins. diam., bears S.83*E., 39 lks.


dist., mkd. 1/2 S 8 B T

A fir, 36 ins. diam., bears S.21*W., 35 lks.

dist., mkd. 1/2 S 7 B T

Desc. 120 ft. over N. slope.

- 43.20 Creek, 1 lk. wide, course W., asc. 400 ft. over S. slope.
- 57.00 Spur, slopes W., asc. 174 ft. along broken SW. slope.
- 73.10 Spur, slopes NW., desc. 84 ft. over N. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 5 ins. in the ground to bedrock, and in a mound of stone to top, for the cor. of secs, 5, 6, 7 and 8, with brass cap mkd.



from which

A fir, 10 ins. diam., bears N.21*E., 31 lks.

dist., mkd. T 26 S R 3 E S 5 B T

A fir, 18 ins. diam., bears S.75*E., 35 lks.

dist., mkd. T 26 S R 3 E S 8 B T

A fir, 20 ins. diam., bears S.43*W., 84 lks.

dist., mkd. T 26 S R 3 E S 7 B T

A fir, 16 ins. diam., bears N.75*W., 46 lks.

dist., mkd. T 26 S R 3 E S 6 B T