

County Surveyor's Record, Douglas County, Oregon

84

Subdivisions of T. 26 S., R. 3 E.

CHAINS	
70.50	Spur, slopes NW., desc. 70 ft. along broken NW. slope.
77.60	Draw, course N., asc. 30 ft. along NE. slope.
80.10	The cor. of secs. 5, 6, 7 and 8.  Land; mountainous.  Soil; rocky, 4th rate.  Timber; fir, hemlock, pine, cedar and yew.  Undergrowth; young fir and hemlock, rhododendron, vinemaple, dog wood and wild currant.
40.00	S.89*57'W., on a random line bet. secs. 6 and 7. Set temp. $\frac{1}{4}$ sec. cor.
78.80	Intersect the W. bdy. of Tp., 19 lks. S. of the cor. of secs. 1, 6, 7, and 12, which is an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.  Thence S.89*55'E., on true line bet. secs. 6 and 7. Desc. 487 ft. over E. slope, along top of spur, through heavy timber and medium undergrowth.
16.40	Spur, slopes S.80'E., desc. 428 ft. over NE. slope.
38.80	True point for the $\frac{1}{4}$ sec. cor., falls in Boulder Breck, 50 lks. wide, course SW., asc. 20 ft. over W. slope.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<p>W C</p> <p><math>\frac{1}{4}</math> <u>S 6</u></p> <p>S 7</p> <p>1931</p> <p style="text-align: right;">from which</p> <p>A yew, 14 ins. diam., bears N.28'E., 16 lks. dist., mkd. W C <math>\frac{1}{4}</math> S 6 B T</p> <p>A fir, 20 ins. diam., bears S.24*W., 58 lks. dist., mkd. W C <math>\frac{1}{4}</math> S 7 B T</p>