

County Surveyor's Record, Douglas County, Oregon

6th Standard Parallel South, through R. 1 E.,
As surveyed By Samuel C. Flint, Deputy Surveyor,
Under contract No. 473, Dated June 5, 1883.

CHAINS	East on S. boundary of Sec. 31
	Var. 18*30'E.
39.00	Summit of mountain.
40.00	Set post 44x4 ins. firmly in the ground for stand. $\frac{1}{4}$ sec. cor. marked S C on N and S faces from which, A fir, 18 ins. in dia., bears N.10*E. 35 lks. dist., marked S C $\frac{1}{4}$ S B T. A fir, 18 ins. in dia., bears S.2*W. 21 lks. dist., marked S C $\frac{1}{4}$ S B T.
65.00	Spring branch 3 lks. wide course North.
65.80	Spring branch 3 lks. wide course North.
68.12	Spring branch 2 lks. wide course North.
80.00	Set post 48x4 ins. firmly in the ground for stand. cor. to secs. 31 and 32 marked S C T 27 S R 1 E on N S 32 E and S 31 on W faces with 5 notches on E and 1 on W edges, from which, A fir, 8 ins. in dia., bears N.25*E. 26 lks. dist., marked T 27 S R 1 E S 32 B T. A fir, 9 ins. in dia., bears N.15*W. 37 lks. dist., marked T 27 S R 1 E S 31 B T. A fir, 8 ins. in dia., bears S.45*W. 15 lks. dist., marked S B T.
	Land 4th rate. Mountainous rough and rocky. Timber fir, hemlock, spruce and pine. Thick underbrush of Cinnamon vine, maple and elk brush.
	East on S. boundary of Sec. 32
	Var. 18*30'E.
36.25	Summit of ridge N. and S.
40.00	Set post 44x4 ins. firmly in the ground for stand. $\frac{1}{4}$ sec. cor. marked S C on N and S. faces from which, A pine, 30 ins. in dia., bears N.20*W. 38 lks. dist. marked S C $\frac{1}{4}$ S B T.