

County Surveyor's Record, Douglas County, Oregon

6th Standard Parallel South through R. 1 E.

CHAINS	<p>A fir, 30 ins. in dia., bears S.35*W. 19 lks. dist., marked S B T.</p> <p>Land 4th rate.</p> <p>Mountainous and rocky.</p> <p>Timber fir, hemlock, spruce and pine.</p> <p>Thick underbrush of mountain laurel vine and maple.</p> <p style="text-align: center;">June 28th 1883</p>
40.00	<p>East on South boundary of Sec. 35.</p> <p>Var. 19*E.</p> <p>Set post 44x4 ins. firmly in the ground for stand. $\frac{1}{2}$ sec. cor. marked S C on N and S faces from which,</p> <p>A pine, 14 ins. in dia., bears S.65*W. 27 lks. dist., marked S C $\frac{1}{2}$ S B T.</p> <p>A pine, 12 ins. in dia., bears N. 43*E. 30 lks. dist., marked S C $\frac{1}{2}$ S B T.</p>
72.70	<p>Peak of Quartz Mountain S.25*E. say 20 chains dist.</p>
79.00	<p>Stream 25 lks. wide course SE.</p>
80.00	<p>Stream 4 lks. wide course south.</p> <p>Set post 48x4 ins. firmly in the ground for stand. cor. to secs 35 and 36 marked S C T 27 S R 1 E on N S 36 on E and S 35 on W faces with 1 notch on E and 5 on W edges from which,</p> <p>A pine, 30 ins. in dia., bears N.40*E. 27 lks. dist., marked T 27 S R 1 E S 36 B T.</p> <p>A chinquapin, 8 ins. in dia., bears N.50*W. 31 lks. dist., marked T 27 S R 1 E S 35 B T.</p> <p>A pine, 24 ins. in dia., bears S.35*W. 33 lks. dist., marked S B T.</p>
	<p>Land 4th rate.</p> <p>Timber fir, hemlock, spruce and pine.</p> <p>Thick underbrush of fir, mountain laurel and vine-maple.</p> <p>Mountainous rough and rocky.</p>