

6th Standard Parallel South through R. 1 E.

CHAINS	<p>East, on S. boundary of Sec. 36. Var. 18*30'E.</p>
38.48	<p>Stream 20 lks. wide, course South. Ascend mountain ridge.</p>
40.00	<p>Set post 44x4 ins. firmly in the ground for stand. $\frac{1}{4}$ sec. cor. marked S C on N. and S. faces, from which, A fir, 20 ins. in dia., bears N.70*W., 28 lks. dist., marked S C $\frac{1}{4}$ S B T A fir, 8 ins. in dia., bears S.50*E., 182 lks. dist., marked S C $\frac{1}{4}$ S B T</p>
80.00	<p>Set post 48x4 ins. firmly in the ground for stand. cor. to Tps. 27 S., R. 1 and 2 E. marked S C T 27 S on N. R 2 E. S 31 on E. and R. 1 E. S 36 on W. faces with 6 notches on N. E. and W. edges, from which, A fir, 30 ins. in dia., bears N.70*E., 28 lks. dist., marked T 27 S R 2 E S 31 B T A fir, 12 ins. in dia., bears N.43*W., 55 lks. dist., marked T 27 S R 1 E S 36 B T A pine, 36 ins. in dia., bears South 10 lks. dist., marked S B T</p> <p>Land, 4th rate. Mountainous and rough. Timber, fir, hemlock, spruce and pine. Thick underbrush of fir, mountain laurel and vine maple. June 29th. 1883.</p>
<p>Willamette Meridian through Tp. 27 S., As surveyed by Homer D. Angell, Deputy Surveyor, Under contract No. 746, dated May 5, 1902.</p>	
<p>From the standard cor. of Tp. 27 S R. 1 E and 1 W which I established June 16, 1902. I run North bet. secs. 31 and 36. Along W. slope through heavy timber and scattering undergrowth.</p>	
8.00	<p>A spring branch 1 lk. wide, course West.</p>
29.00	<p>Top of ridge point, bears E. and W. descend. Difference between measurement of 40.00 chains by two sets of chainmen is 10 lks., position of middle point.</p> <p style="text-align: center;">By 1st. set---40.05 By 2nd set----39.95</p>
40.00	<p>The mean of which is, Set a basalt stone, 15x10x5 ins., 10 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which, A fir, 18 ins. in dia., bears S.85*E., 37 lks. dist., marked $\frac{1}{4}$ S 31 B T</p>