

County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through Tp. 27 S.

CHAINS	A fir, 16 ins. in dia., bears N.72 $\frac{1}{2}$ *W., 28 lks. dist., marked $\frac{1}{4}$ S 36 B T
44.25	A spring branch, 15 lks. wide, course NW. Ascend.
71.50	Top of ridge, 250 ft. high, bears E. and W. Descend
	Difference between chaining of 80.00 chains by two sets chainmen is 14 lks., position of middle point
	By 1st set---80.07
	By 2nd set---79.93
	The mean of which is
80.00	Set a basalt stone, 15x12x8 ins. 10 ins. in ground for cor. of secs. 25, 30, 31 and 36 marked with 5 notches N and 1 in S. edges, from which,
	A hemlock, 12 ins. in dia., bears N.11*E., 7 lks. dist., marked T 27 S R 1 E S 30 B T
	A hemlock, 8 ins. in dia., bears S.63*E., 25 lks. dist., marked T 27 S R 1 E S 31 B T
	A hemlock, 8 ins. in dia., bears S.45*W., 27 lks. dist., marked T 27 S R 1 W S 36 B T
	A hemlock, 12 ins. in dia., bears N.68*W., 20 lks. dist., marked T 27 S R 1 W S 25 B T
	Land, mountainous.
	Soil, stoney and 3rd rate.
	Timber, fir, pine, laurel and hemlock.
	Undergrowth laurel, willow and wild cherry.
	Mountainous or heavily timbered land or land covered with dense undergrowth. 80.00 chains. July 5, 1902.
	At the cor. of secs. 25, 30, 31 and 36. Thence I run North bet. secs. 25 and 30. Descend through heavy timber and dense undergrowth.
11.60	A spring branch, 3 lks. wide, course W.
18.25	Top of spur thence along W. slope.
20.00	A fir, 20 ins. in dia., on line I mark with two notches N. and S. sides.
35.00	Steep descent. Difference between measurement of