

Willamette Meridian through T 27 S

CHAINS	A fir, 26 ins. in dia., bears S.68*W. 24 lks., dist., marked $\frac{1}{2}$ S 12 B T.
41.00	Bearing of hill changes to E and W.
62.00	Top of divide, 1500 ft. high, sudden descent over precipitous ground, bearing of hill, N and S. Difference between measurement of 80.00 chs. by two sets of chainmen is 12 lks. position of middle point, By 1st set---80.06 By 2nd set---79.94
	The mean of which is
80.00	Set a basalt stone, 15x10x6 ins. 10 ins. in ground for cor. of secs. 1,6,7, and 12, marked with 1 notch on N and 5 notches on S edges, from which,
	A fir, 10 ins. in dia., bears N.15*E. 16 lks. dist., marked T 27 S R 1 E S 6 B T.
	A fir, 8 ins. in dia., bears S.85*E. 45 lks. dist., marked T 27 S R 1 E S 7 B T.
	A fir, 30 ins. in dia., bears S.20*W. 30 lks. dist., marked T 27 S R 1 W S 12 B T.
	A fir, 8 ins. dia., bears N.89*W. 6 lks. dist., marked T 27 S R 1 W S 1 B T.
	Land mountainous.
	Soil, stoney and 3rd rate.
	Timber, fir, pine, laurel and hemlock.
	Undergrowth laurel and huckleberry.
	Mountainous or heavily timbered land or land covered with dense undergrowth. 80.00 chains.
	North bet. secs. 1 and 5.
	Descend through scattering timber and dense undergrowth.
2.50	A spring branch, 2 lks. wide, course S.75*E.
7.00	Dry bed of stream, course S.35*E. ascend hillside bears SE and NW.
30.00	Descend into turn.