


Dependent Resurvey of the Willamette Meridian through T 27 S.

CHAINS

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked.



from which,

A fir, 20 ins. in dia., bears S.85*E., 37 lks. dist., marked $\frac{1}{4}$ S 31 B T (old B T.)

A fir, 18 ins. in dia., bears N.72 $\frac{1}{2}$ *W., 28 lks. dist., marked $\frac{1}{4}$ S 36 B T. (old B T)

Thence,

N.1*27'W.,

Descend 84 ft. over N. slope.

4.10 Creek, 12 lks. wide, course NW.

Ascend 561 ft. over broken SW. slope.

13.40 Small spur, slopes W.


32.00 Spur, slopes W.

Descend 207 ft. over N. slope.

39.59 Intersect the cor. of secs. 25,30,31 and 36, which is basalt stone, 12x8x7 ins. above ground, marked 5 notches on the N. and 1 notch on the S. edge.

Alongside of old cor. stone;

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 25 and 36 only, with brass cap marked.



from which,

A hemlock, 16 ins. in dia., bears N.11*E., 7 lks. dist., marked T 27 S R 1 E S 30 B T (old B.T.)

A hemlock, 12 ins. in dia., bears S.63*E. 25 lks. dist., marked T 27 S R 1 E S 31 B T (old B.T.)

A hemlock, 10 ins. in dia., bears S.45*W. 27 lks. dist., marked T 27 S R 1 W S 36 B T (old B.T.)