

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian through T 27 S.

CHAINS

A hemlock, 14 ins. in dia., bears N.68*W. 20 lks. dist.,
marked T 27 S R 1 W S 25 B T (old B.T.)

I change this cor. to refer to secs. 25 and 36 only
destroying the old scribe marks on the NE. and SE.
bearing trees.

Land, rolling and mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, rhododendron and yinemaple.

N.0*09*W., on the E. bdy. of sec. 25.

Over mountainous land, through timber,

.38 The closing cor. of secs. 30 and 31, later determined
and hereinafter described.

Descend 390 ft. over N. slope.

11.70 Creek, 3 lks. wide, course NW.

Ascend 224 ft. over S. slope.

18.20 Spur, slopes SW.

Descend 40 ft. over N. slope.

22.10 Bottom of descent.

Ascend 111 ft. over broken SW. slope.

26.50 Spur, slopes SW.

30.50 Spur, slopes NW.

Descend 491 ft. over NW. slope.

39.75 Intersect the original $\frac{1}{4}$ sec. cor. established for secs.
25 and 30, which is a basalt stone 12x6x10 ins. above
ground, marked $\frac{1}{4}$ on W. face.

I change this cor. to refer to secs. 25 only, obliterating
the marks on the old NE. bearing tree.

Alongside of old stone cor;

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor. of sec. 25 only, with
brass cap marked.

$\frac{1}{4}$ S 25

1927

from which,