

Dependent Resurvey of the Willamette Meridian through T 27 S.

CHAINS

A cedar, 20 ins. in dia., bears N.12*E., 31 lks. dist.,
marked $\frac{1}{4}$ S 30 B T. (Old B.T.)

A hemlock, 16 ins. in dia., bears N.70*W., 12 lks. dist.,
marked $\frac{1}{4}$ S 25 B T (old B.T.)

A cedar, 8 ins. in dia., bears S.16*W., 54 lks. dist.,
marked $\frac{1}{4}$ S 25 B T.

Thence,

North.

.60 Creek, 10 lks. wide, course NW.

.81 Point for the $\frac{1}{4}$ sec. cor. of sec. 30 only, later determined
falls on steep bank on the N. side of creek, where it is
impracticable to establish cor.

1.00 Set an iron post, 3 ft. long, 1 in in dia., 12 ins. in
the ground to bedrock, supported in a mound of stone
for the witness $\frac{1}{4}$ sec. cor. of sec. 30 only, with brass
cap marked.

$\frac{1}{4}$ S30
| WC
1927

from which,

A cedar, 20 ins. in dia., bears N.88 $\frac{1}{2}$ *E., 77 lks. dist.,
marked W C $\frac{1}{4}$ S 30 B T.

A hemlock, 8 ins. in dia., bears S.65*E., 36 lks. dist.,
marked W C $\frac{1}{4}$ S 30 B T

Ascend 1157 ft. over S. slope.

22.00 East edge of bluff, bears E. and W. faces S.

32.00 Ridge, bears NE. and SW. descend 222 ft. over N. slope.

39.69 Intersect the old cor. established for secs. 19,24,25
and 30, which is a basalt stone 6x10x12 ins. above
ground, marked with 4 notches on the N. and 2 notches
on the S. edges.

I change this cor. to refer to secs. 24 and 25 only,
obliterating the scribe marks on the NE. and SE. bearing
trees.

Along side of old stone cor;

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in
the ground, for the cor. of secs. 24 and 25 only, with