


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian through T 27 S.

CHAINS

brass cap marked.



from which,

A fir, 18 ins. in dia., bears N.82*E. 61 lks. dist., marked T 27 S R 1 E S 19 B T (old B.T.)

A fir, 10 ins. in dia., bears S.81*E., 61 lks. dist., marked T 27 S R 1 E S 30 B T (old B.T.)

A fir, 35 ins. in dia., bears S.25*W., 30 lks. dist., marked T 27 S R 1 W S 25 B T (old B.T.)

A fir, 34 ins. in dia., bears N.80*W., 10 lks. dist., marked T 27 S R 1 W S 24 B T (old B.T.)

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, rhododendron and vinemaple.

N.0*26'E., on the E. bdy. of sec. 24.

Over mountainous land, through timber.

Descend 181 ft. over N. slope.

1.30 point for the closing cor. of secs. 19 and 30, later determined and hereinafter described.

4.40 Small stream, 1 lk. wide, course NW.

Ascend 234 ft. over S. slope

14.30 Spur, slopes SW.

Descend 113 ft. over NW. slope.

21.60 Creek, 2 lks. wide, course NW.

Ascend 329 ft. over broken S. slope.

40.12 Intersect the old 1/4 sec. cor. established for secs. 19 and 24, which is a basalt stone 9x6x10 ins. above ground, marked 1/4 on W. face.

I change this cor. to refer to sec. 24 only, destroying the old scribe marks on the SE. bearing tree.

Along side of old stone cor;