

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian through T 27 S.

CHAINS

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 24 only, with brass cap marked.

$$\begin{array}{c} | \\ \frac{1}{4} \text{ S24} \\ | \\ 1927 \end{array}$$

from which,

A fir, 22 ins. in dia., bears S.61\*E., 30 lks. dist., marked  $\frac{1}{4}$  S 19 B T (old B.T.)

A fir, 30 ins. in dia., bears N.59\*W., 22 lks. dist., marked  $\frac{1}{4}$  S 24 B T (old B.T.)

A fir, 32 ins. in dia., bears S.40\*W., 40 lks. dist., marked  $\frac{1}{4}$  S 24 B T (new B.T.)

Thence,

N.1\*09'E.,

Ascend 160 ft. over S. slope.

1.34 Point for the  $\frac{1}{4}$  sec.cor. of sec. 19 only, later determined.

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 19 only, with brass cap marked.

$$\begin{array}{c} | \\ \frac{1}{4} \text{ S19} \\ | \\ 1927 \end{array}$$

from which,

A fir, 28 ins. in dia., bears N.47\*E., 67 lks. dist., marked  $\frac{1}{4}$  S 19 B T.

A fir, 14 ins. in dia., bears S.39\*E., 80 lks. dist., marked  $\frac{1}{4}$  S 19 B T.

1.61 Clover Creek Way Trail, bears E. and W.

10.40 Ridge, bears NE. and SW.

Descend 227 ft. over NW. slope.

15.40 Along W. slope of mountains.

32.00 Descend 374 ft. over NW. slope.

39.69 Intersect the old cor. established for secs. 13,18,19 and 24, which is a basalt stone 8x8x10 ins. above ground, marked with 3 notches on the N. and 3 notches on the S. edges.