

Dependent Resurvey of the Willamette Meridian through T 27 S

CHAINS

I change this cor. to refer to secs. 13 and 24 only, obliterating the old scribe marks on the NE. and SE. bearing trees.

Along side of old stone cor;

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 13 and 24 only, with brass cap marked.

T27S	T27S
S13	S19
S24	
R1W	R1E
1927	

from which,

A yew, 12 ins. in dia., bears N.47 $\frac{1}{2}$ *E., 20 lks. dist., marked T 27 S R 1 E S 18 B T (old B.T.)

A fir, 34 ins. in dia., bears S.6*E., 19 lks. dist., marked T 27 S R 1 E S 19 B T (old B.T.)

A fir, 34 ins. in dia., bears S.37*W., 60 lks. dist., marked T 27 S R 1 W S 24 B T (old B.T.)

A fir, 30 ins. in dia., bears N.74*W., 25 lks. dist., marked T 27 S R 1 W S 13 B T.

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, cedar, pine and yew.

Undergrowth, rhododendron and vine maple.

North, on the E. bdy, of sec. 13.

Over mountainous land, through timber.

Descend 331 ft. over NW. slope.

1.82 Point for the closing cor. of secs. 18 and 19, later determined and hereinafter described.

15.00 Descend 600 ft. over NE. slope.

34.30 Little River, 28 lks. wide, course NW.

Ascend 88 ft. over SW. slope.

36.00 Little River Trail, bears E. and W.

40.01 Intersect the old $\frac{1}{4}$ sec. cor. established for secs. 13 and 18, which is a basalt stone 10x8x7 ins. above ground, marked $\frac{1}{4}$ on the W. face.