


Dependent Resurvey of the Willamette Meridian through T 27 S.

CHAINS

I change this cor. to refer to sec. 13 only, obliterating the old scribe marks on the SE. bearing tree. Along side of old cor. stone;  
Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor., of sec. 13 only, with brass cap marked.



from which,  
A fir, 28 ins. in dia., bears S.70\*E., 30 lks. dist., marked  $\frac{1}{4}$  S 18 B T (old B.T.)  
A fir, 14 ins. in dia., bears S.15\*W., 38 lks. dist., marked  $\frac{1}{4}$  S 13 B T (old B.T.)  
A fir, 14 ins. in dia., bears N.79\*W., 44 lks. dist., marked  $\frac{1}{4}$  S 13 B T.


Thence,

N.0\*09'E.

Ascend 420 ft. over broken SW. slope.

1.76 Point for the  $\frac{1}{4}$  sec. cor. of sec. 18 only, later determined.

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 18 only, with brass cap marked.



from which,  
A fir, 20 ins. in dia., bears N.47\*E., 37 lks. dist., marked  $\frac{1}{4}$  S 18 B T.  
A fir, 36 ins. in dia., bears S.32\*E., 73 lks. dist., marked  $\frac{1}{4}$  S 18 B T.

31.00 Ascend 297 ft. over S. slope.

38.87 Intersect the old cor. established for secs. 7,12,13 and 18, which is a basalt stone 14x4x8 ins. above ground, marked with 2 notches on the N. and 4 notches on the S. edges.