

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian through T 27 S.

CHAINS
32.30

Creek, 2 lks. wide, course SW.

Ascend 173 ft. over S. slope.

39.87-

Intersect the old $\frac{1}{4}$ sec. cor., established for secs. 7 and 12, which is a basalt stone 8x6x6 ins. above ground, marked $\frac{1}{4}$ on the W. face.

I change this cor. to refer to sec. 12 only, obliterating the old scribe marked of the SE. bearing tree.

Along side of old stone cor;

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap marked.

$$\begin{array}{c} \frac{1}{4} S 12 \\ | \\ 1927 \end{array}$$

from which,

A fir, 22 ins. in dia., bears S.45*E., 17 lks. dist., marked $\frac{1}{4}$ S 7 B T (old B.T.)

A fir, 30 ins. in dia., bears S.68*W., 24 lks. dist., marked $\frac{1}{4}$ S 12 B T (old B.T.)

A fir, 28 ins. in dia., bears N.69*W., 22 lks. dist., marked $\frac{1}{4}$ S 12 B T

Thence,

N.0*43'E.

Ascend 741 ft. over broken SW. slope.

2.78

Point for the $\frac{1}{4}$ sec. cor. of sec. 7 only, later determined.

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 7 only, with brass cap marked.

$$\begin{array}{c} \frac{1}{4} S 7 \\ | \\ 1927 \end{array}$$

from which,

A fir, 26 ins. in dia., bears N.45*E., 39 lks. dist., marked $\frac{1}{4}$ S 7 B T.

A fir, 26 ins. in dia., bears S.62*E., 42 lks. dist., marked $\frac{1}{4}$ S 7 B T.

17.90

Small spur, slopes SE.