

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian through T 27 S

CHAINS  
21.70

Spur, slopes E.  
Descend 670 ft. over NE. slope, through dense undergrowth.

22.80

Bluff, 40 ft. high, bears E. and W. faces N.

36.10

Small spur, slopes NE.

39.71

Intersect the old cor. established for secs. 1,6,7 and 12, which is a basalt stone 12x6x10 ins. above ground, marked with one notch on the N. and 5 notches on the S. edges.

I change this cor. to refer to secs. 1 and 12 only, destroying the scribe marks on the NE. and SE. bearing trees.

Alongside of old cor. stone;

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 1 and 12 only, with brass cap marked.

T27S	T27S
S 1	S 7
S12	
RLW	RIE
1927	

from which,

A fir, 12 ins. in dia., bears N.15\*E., 16 lks. dist., marked T 27 S R 1 E S 6 B T (old B.T.)

A fir, 12 ins. in dia., bears S.85\*E., 45 lks. dist., marked T 27 S R 1 E S 7 B T (old B.T.)

A fir, 34 ins, in dia., bears S.20\*W., 30 lks. dist., marked T 27 S R 1 W S 12 B T (old B.T.)

A fir, 10 ins. in dia., bears N.89\*W., 6 lks. dist., marked T 27 S R 1 W S 1 B T (old B.T.)

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, huckleberry, vine maple and willow.

N.0\*04'W., on the E. bdy. of sec. 1.

Over mountainous land, through timber.

Descend 126 ft. over NW. slope.

2.60

Small stream, 1 lk. wide, course NE.