

Dependent Resurvey of the Willamette Meridian T 27 S.

CHAINS	
	Ascend 50 ft. over S. slope.
2.87	Point for the closing cor. of secs. 6 and 7, later determined and hereinafter described.
5.00	Small spur, slopes NE. Descend 38 ft. over N. slope.
9.40	Draw, course NE.
17.80	Draw, course SE. Ascend 541 ft. over SW. slope.
29.00	Spur, slopes SE., enter burned over area. Descend 132 ft. over N. slope.
32.50	Draw, course E. Ascend 136 ft. over S. slope.
37.40	Spur, slopes SE. Descend 43 ft. over N. slope.
39.80	Intersect the old $\frac{1}{4}$ sec. cor. established for secs. 1 and 6, which is a basalt stone 10x4x7 ins. above ground, marked $\frac{1}{4}$ on W. face. This cor. will hereafter refer to sec. 1 only. Alongside of old stone cor; Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., of sec. 1 only with brass cap marked.
	$\frac{1}{4}$ S 1   1927
	Raise a mound of stone, with a 3 ft. base, 2 ft. high W. of cor., as no bearing trees were available.
	Thence, North,
1.00	Small ravine, course SE. Ascend 103 ft. over S. slope.
3.07	Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, later determined. Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap marked.