

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian through T 27 S.

CHAINS	$\frac{1}{4}$ S 6 1927												
	From which, A fir, 6 ins. in dia., bears N.53*E., 120 lks. dist., marked $\frac{1}{4}$ S 6 B T. A fir, 8 ins. in dia., bears N.84*E., 244 lks. dist., marked $\frac{1}{4}$ S 6 B T.												
6.40	Small spur, slopes SE. Descend 75 ft. over N. slope.												
10.20	Small creek, 1 lk. wide, course SE. Ascend 254 ft. over S. slope.												
17.10	Small spur, slopes SE. Descend 45 ft. over N. slope.												
19.70	Draw, course SE. Ascend 262 ft. over SW. slope.												
26.37	Emile trail, and telephone line, bear E. and NW.												
27.30	Ridge, bears E. and W. Descend 241 ft. over N. slope.												
38.75	Intersect the old Tp. cor., established for Tps. 26 and 27 S., Rs. 1 W. and 1 E., which is a basalt stone 18x 12x10 ins. above ground, marked with 6 notches on the N., S., E. and W. edges. I change this cor. to refer to Tps. 26 and 27 S R 1 W only, destroying the marks on the E. side of the stone cor., and obliterate the old scribe.marks on the NE. and SE. bearing trees. Along side of old cor. stone. Set an iron post, 3 ft. long, 3 ins. in dia., 27 ins. in the ground,,for the cor. of Tps. 26 and 27 S., R 1 W only, with the brass cap marked.												
	<table border="0"> <tr> <td>T26S</td> <td></td> </tr> <tr> <td>R1W</td> <td>T27S</td> </tr> <tr> <td>S36</td> <td>S 6</td> </tr> <tr> <td>S 1</td> <td></td> </tr> <tr> <td>T27S</td> <td>R1E</td> </tr> <tr> <td></td> <td>1927</td> </tr> </table>	T26S		R1W	T27S	S36	S 6	S 1		T27S	R1E		1927
T26S													
R1W	T27S												
S36	S 6												
S 1													
T27S	R1E												
	1927												