

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian through T 27 S.

## CHAINS

from which,

A fir, 20 ins. in dia., bears N.83°E., 75 lks. dist.,  
marked T 26 S R 1 E S 1 B T (old B.T.)

A fir, 28 ins. in dia., bears S.21½°E., 27 lks. dist.,  
marked T 27 S R 1 E S 6 B T (old B.T.)

A fir, 24 ins. in dia., bears S.55½°W., 55 lks. dist.,  
marked T 27 S R 1 W S 1 B T (old B.T.)

A fir, 28 ins. in dia., bears N.61°W., 48 lks. dist.,  
marked T 26 S R 1 W S 36 B T (old B.T.)

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, Huckleberry, rhododendron and willow.

Survey of East Boundary of T. 27 S., R. 1 E.

From the standard Tp. cor. of T. 27 S Rs. 1 and 2 E. as  
described in the field notes of T 28 S R 1 E .

Thence, N. bet. secs. 31 and 36.

Over mountainous land, through timber and dense undergrowth.

Ascend 226 ft. over SW. slope.

16.08 Quartz Creek Way Trail, bears NE. and SW. on spur,  
slopes SW.

Thence along W. slope through open timber.

14.60 Spur, slopes W.

Descend 149 ft. over NW. slope.

22.30 Top of bluff, 60 ft. high, bears E. and W., faces N.

23.60 Creek, 2 lks. wide, course SW.

Ascend 234 ft. over SW. slope..

36.40 Spur, slopes W.

Descend 94 ft. over NW. slope through timber and medium  
dense undergrowth..

40.00 Set an iron post, 3 ft. long, 1 in in dia., 27 ins. in  
the ground, for the ¼ sec. cor., with brass cap marked.