

County Surveyor's Record, Douglas County, Oregon

Survey of the East Boundary of T. 27 S R 1 E.

CHAINS	<p>North, bet. secs. 25 and 30.</p> <p>Over mountainous land, through timber and dense undergrowth.</p> <p>Descend 59 ft. over N. slope.</p> <p>4.10 Small stream, 1 lk. wide, course SW.</p> <p>Ascend 698 ft. over broken S. slope.</p> <p>6.90 Small spur, slopes SW.</p> <p>14.20 Spring branch, 2 lks. wide, course SW.</p> <p>18.50 Spring branch, 2 lks. wide, course SW.</p> <p>23.00 Small spur, slopes SW.</p> <p>31.40 Emile Trail, bears SE. and NW.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground to bedrock, supported in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap marked.</p> <div style="text-align: center;"> <p style="margin: 0;"> \uparrow S25 S30 1927 </p> </div> <p>from which,</p> <p>A fir, 48 ins. in dia., bears N.68*E., 44 lks. dist., marked $\frac{1}{4}$ S 30 B T.</p> <p>A fir, 12 ins. in dia., bears S.86$\frac{1}{2}$*W., 34 lks. dist., marked $\frac{1}{4}$ S 25 B T.</p> <p>Ascend 281 over S. slope.</p> <p>42.62 Stock driveway, bears E. and W.</p> <p>51.50 Snow Bird Mountain, on ridge, bears E. and W.</p> <p>Descend 176 ft. over broken NW. slope.</p> <p>60.60 Spring branch, 1 lk. wide, course W.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 19,24,25 and 30, with brass cap marked.</p> <div style="text-align: center;"> <p style="margin: 0;"> T27S R1E R2E S24 S19 S25 S30 1927 </p> </div> <p>from which,</p> <p>A fir, 34 ins. in dia., bears N.35*E., 59 lks. dist., marked T 27 S R 2 E S 19 B T.</p>
--------	---