


County Surveyor's Record, Douglas County, Oregon

Survey of the East boundary of T 27 S R 1 E.

CHAINS  
40.00

Set an iron post, .3 ft. long, 1 in. in dia., 8 ins. in the ground to bedrock, supported in a mound of stone, for the 1/4 sec. cor., with brass cap marked.



from which,

A fir, 6 ins. in dia., bears S.81\*E., 8 lks. dist., marked 1/4 S 18 B T.

A fir, 5 ins. in dia., bears S.89\*W., 39 lks. dist., marked 1/4 S 13 B T.

Descend 153 ft. over steep N. slope.

43.90 Calf Creek, 12 lks. wide, course SE.

Ascend 91 ft. over S. slope.

47.80 Spur, slopes SE.

Descend 45 ft. over N. slope.

48.90 Creek, 1 lk. wide, course SE.

Ascend 368 ft. over broken S. slope.

74.00 Top of ridge, bears NE. and SW., thence, over rolling top.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor, of secs. 7,12,13 and 18, with brass cap marked.



from which,

A fir, 30 ins. in dia., bears N.46\*E., 9 lks. dist., marked T 27 S R 2 E S 7 B T.

A hemlock, 12 ins. in dia., bears S.18\*E., 48 lks. dist., marked T 27 S R 2 E S 18 BT.

A fir, 36 ins. in dia., bears S.52\*W., 13 lks. dist., marked T 27 S R 1 E S 13 B T.

A fir, 8 ins. in dia., bears N.59\*W., 17 lks. dist., marked T 27 S R 1 E S 12 B T.