

County Surveyor's Record, Douglas County, Oregon

Survey of the North Boundary of T 27 S R 1 E

CHAINS

Descend 274 ft. over NW. slope.

20.00 Bottom of descent.

Ascend 116 ft. over NE. slope.

27.14 Spur, slopes N.

Descend 595 ft. over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked.

$\frac{1}{4}$ S35
S 2
1927

from which,

A fir, 36 ins. in dia., bears N.13*E., 29 lks. dist., marked $\frac{1}{4}$ S 35 B T.

A fir, 38 ins. in dia., bears S.40*W., 62 lks. dist., marked $\frac{1}{4}$ S 2 B T.

Descend 361 ft. over W. slope.

52.00 Limpy Creek, 10 lks. wide, course NE.

Ascend 1020 ft. over SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 2,3,34 and 35, with brass cap marked.

T26SR1E
S34|S35
S 3|S 2
T27S
1927

from which,

A fir, 30 ins. in dia., bears N.48*E., 34 lks. dist., marked T 26 S R 1 E S 35 B T.

A fir, 18 ins. in dia., bears S.50*E., 65 lks. dist., marked T 27 S R 1 E S 2 B T.

A fir, 24 ins. in dia., bears S.60*W., 65 lks. dist., marked T 27 S R 1 E S 3 B T.

A chinquapin, 7 ins. in dia., bears N.15*W., 45 lks. dist., marked T 26 S R 1 E S 34 B T.