

County Surveyor's Record, Douglas County, Oregon

Survey of the North Boundary of T. 27 S., R 1 E.

CHAINS	<p>West, bet. secs. 6 and 31.</p> <p>Oven mountainous land, through timber and brush.</p> <p>Ascend 62 ft. over E. slope.</p> <p>1.60 Spur, slopes S. descend 87 ft. over W. slope.</p> <p>14.50 Ravine, course SE.</p> <p>Ascend 253 ft. over broken E. slope.</p> <p>21.25 Emile Trail and telephone line, bear NE. and SW.</p> <p>23.00 Spur, slopes S., descend 192 ft. over W. slope.</p> <p>24.74 Emile Trail and telephone line, bears SE. and NW.</p> <p>27.60 Bluff, 40 ft. high, bears SE. and NW., faces SW.</p> <p>30.40 Ravine, course S.</p> <p>Ascend 216 ft. over broken SE. slope.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. in dia., 4 ins. in the ground to bedrock, supported in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap marked.</p> <p style="text-align: center;"> $\frac{1}{4} \frac{S31}{S6}$ 1927 </p> <p>from which,</p> <p>A fir, 14 ins. in dia., bears N.8*E., 11 lks. dist., marked $\frac{1}{4}$ S 31 B T.</p> <p>A fir, 14 ins. in dia., bears S.53*W., 32 lks. dist., marked $\frac{1}{4}$ S 6 B T.</p> <p>40.20 Ridge, bears NE. and SW.</p> <p>Descend 500 ft. over NW. slope.</p> <p>41.40 Emile Trail and telephone line, bear NE. and SW.</p> <p>73.70 Draw, course NW., ascend 45 ft. over E. slope.</p> <p>78.34 Spur, slopes NW., thence along N. slope.</p> <p>79.28 Intersect the Willamette Meridian, 4.63 chs. N.0*27'W., of the cor. of Tps. 26 and 27 S., R 1 W.</p> <p>(Note; For the retracement and resurvey of the Willamette Meridian through T 26 S., see field notes of the survey of T 26 S R 1 E.)</p> <p>At point of intersection:</p> <p>Set an iron post, 3 ft. long, 3 ins. in dia., 10 ins. in the ground to bedrock, supported in a mound of stone, with a 5 ft. base, 2 ft. high, for the closing of T. cor. of Tps. 26 and 27 S., R 1 E., with brass cap marked.</p>
--------	--