

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 27 S. R. 1 E.

CHAINS  
80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 11, 12, 13 and 14 with brass cap marked.

T27SR1E  
S11 | S12  
S14 | S13  
1927

from which,

A fir, 28 ins. in dia., bears N.30\*E., 44 lks. dist., marked T 27 S R 1 E S 12 B T.

A Fir, 22 ins. in dia., bears S.57\*E., 51 lks. dist., marked T 27 S R 1 E S 13 B T.

A fir, 14 ins. in dia., bears S.63\*W., 59 lks. dist., marked T 27 S R 1 E S 14 B T.

A fir, 20 ins. in dia., bears N.33\*W., 62 lks. dist., marked T 27 S R 1 E S 11 B T.

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock and pine.

Undergrowth, rhododendron, wine maple and chinquapin.

40.00

S.89\*52'E., on a random line bet. secs. 12 and 13.

Set. temp. 1/4 sec. cor.

79.76

Intersect the E. bdy of the Tp. 2 lks. S. of the cor. of secs. 7, 12, 13 and 18, hereinbefore described.

Thence,

N.89\*53'W., on a true line bet. secs. 12 and 13.

Over mountainous land, through timber and brush.

Ascend 46 ft. over NE. slope.

3.30

Spur, slopes SE.

Descend 30 ft. over W. slope.

18.00

Bottom of descent, bears N. and S.

Ascend 226 ft. over gradual broken E. slope.

36.60

Creek, 4 lks. wide, course S., ascend 49 ft. over E. slope.

39.88

Set an iron post, 3 ft. long, 1 in. in dia. 27 ins. in the ground, for the 1/4 sec. cor., with the brass cap marked.

1/4 S12  
S13  
1927