

Subdivisions, T. 27 S., R. 1 E.

CHAINS	Ascend 324 ft. over E. slope.
40.06	Set an iron post, 3 ft. long, 1 in. in dia., 2 ins. in the ground to bedrock, supported in a mound of stone with a 6 ft. base, 2½ ft. high, for the ¼ sec. cor., with brass cap marked.
	$\frac{1}{4} \frac{S 1}{S 12}$ 1927
	from which, A fir, 10 ins. in dia., bears S.79*E., 11 lks. dist., marked ¼ S 12 B T. A fir, 6 ins. in dia., bears N.16*W., 16 lks. dist., marked ¼ S 1 B T.
	Ascend 830 ft. over broken E. slope.
51.40	Bluff, 90 ft. high, bears N. and S., faces E.
78.10	Spur, slopes S.
	Descend 16 ft. over SW. slope.
80.12	The cor. of secs. 1, 2, 11 and 12.
	Land, mountainous.
	Soil, rocky loam, 3rd rate.
	Timber, fir, cedar, pine and hemlock.
	Undergrowth, chinquapin, rhododendron and vine maple.
	North, on a random line bet. secs. 1 and 2.
40.00	Set temp. ¼ sec. cor.
80.08	Intersect the N. bdy. of the Tp., 14 lks. W. of the cor. of secs. 1, 2, 35 and 36, hereinbefore described.
	Thence,
	S.0*06*W., on a true line bet. secs. 1 and 2.
	Over mountainous land, through timber and brush.
	Descend 85 ft. over SE. slope.
6.50	Draw, course E.
	Ascend 138 ft. over NE. slope.
17.10	Spur, slopes SE.
	Descend 372 ft. over S. slope.