

County Surveyor's Record, Douglas County, Oregon

Subdivisions. T. 27 S. R. 1 E.

CHAINS

65.50 Emile Trail, and telephone line, bears E. and W.
 Descend 338 ft. over broken N. slope.

73.80 Draw, course NE.

78.10 Draw, course E.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in
 the ground, for the cor. of secs. 3, 4, 9 and 10, with
 brass cap marked.

T27SR1E	
S 4	S 3
S 9	S 10
1928	

from which,

A fir, 24 ins. in dia., bears N.25*E., 33 lks. dist.,
 marked T 27 S R 1 E S 3 B T

A fir, 30 ins. in dia., bears S.36*E., 47 lks. dist.,
 marked T 27 S R 1 E S 10 B T

A fir, 36 ins. in dia., bears S.59*W., 55 lks. dist.,
 marked T 27 S R 1 E S 9 B T

A fir, 20 ins. in dia., bears N.32*W., 52 lks. dist.,
 marked T 27 S R 1 E S 4 B T

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, rhododendron, vine maple and chinquapin.

40.00 N.89*45'E., on a random line bet. secs. 3 and 10.
 Set temp. 1/2 sec. cor.

79.98 Intersect the N. and S. line 9 lks. S. of the cor. of
 secs. 2, 3, 10 and 11.

Thence,

S.89*41'W., on a true line bet. secs. 3 and 10.
 Over rolling land, through timber and undergrowth.
 Ascend 58 ft. over NE. slope.

3.20 Spur, slopes N.
 Descend 127 ft. over broken NW. slope.