

Subdivisions. T. 27 S. R. 1 E.

CHAINS

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 20, 21, 28 and 29, with brass cap marked.

T27SR1E
 S20 | S21
 S29 | S28
 1927

from which,

A fir, 28 ins. in dia., bears N.78*E., 52 lks. dist., marked T 27 S R 1 E S 21 B T

A fir, 14 ins. in dia., bears S.28*E., 62 lks. dist., marked T 27 S R 1 E S 28 B T

A fir, 14 ins. in dia., bears S.78*W., 51 lks. dist., marked T 27 S R 1 E S 29 B T

A fir, 20 ins. in dia., bears N.12*W., 94 lks. dist., marked T 27 S R 1 E S 20 B T

Land, rolling.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock and pine.

Undergrowth, vine maple, rhododendron and chinquapin.

N.89*45'E., on a random line bet. secs. 21 and 28.

40.00

Set temp. 1/4 sec. cor.

80.08

Intersect the N. and S. line, 19 lks. N. of the cor. of secs. 21, 22, 27 and 28.

Thence,

S.89*53'W., on a true line bet. secs. 21 and 28.

Over rolling land, through timber and brush.

24.30

Spur, slopes NW.

Descend 139 ft. over W. slope.

36.80

Creek, 2 lks. wide, course SW.

40.04

A fir, 30 ins. in dia., for the 1/4 sec. cor., I mark 1/4 S 21 on the N., and S 28 on the S. sides.