

Subdivisions, T. 27 S., R. 1 E.

CHAINS 76.00	<p>Spur, slopes W.</p> <p>Descend 47 ft. over NW. slope.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 8, 9, 16 and 17, with brass cap marked.</p> <div style="text-align: center;"> <p>T27SR1E S 8 S 9 S17 S16 1927</p> </div> <p>from which,</p> <p>A fir, 18 ins. in dia., bears N.56*E., 60 lks. dist., marked T 27 S R 1 E S 9 B T</p> <p>A fir, 22 ins. in dia., bears S.57½*E., 35 lks. dist., marked T 27 S R 1 E S 16 B T</p> <p>A fir, 24 ins. in dia., bears S.33*W., 36 lks. dist., marked T 27 S R 1 E S 17 B T</p> <p>A fir, 22 ins. in dia., bears N.49*W., 63 lks. dist., marked T 27 S R 1 E S 8 B T</p> <p>Land, mountainous and rolling.</p> <p>Soil, rocky loam, 3rd rate.</p> <p>Timber, fir, hemlock, pine and cedar.</p> <p>Undergrowth, vine maple, rhododendron, and chinquapin.</p>
40.00	<p>N.89*48'E., on a random line bet. secs. 9 and 16.</p> <p>Set temp. ½ sec. cor.</p>
79.92	<p>Intersect the N. and S. line, 5 lks. S. of the Cor. of secs. 9, 10, 15 and 16.</p> <p>Thence,</p> <p>S.89*46'W., on a true line bet. secs. 9 and 16.</p> <p>Over rolling land, through timber and brush.</p> <p>Descend 400 ft. over broken W. slope</p>
24.30	<p>Draw, course S.</p>
25.50	<p>Spur, slopes S.</p> <p>Descend 88 ft. over SW. slope.</p>
30.10	<p>Creek, 10 lks. wide, course S.</p>