

County Surveyor's Record, Douglas County, Oregon

Subdivisions T. 27 S. R. 1 E.

CHAINS	
	Over mountainous land, through timber and brush. Descend 154 ft. over broken N. slope.
1.00	Creek, 6 lks. wide, course NE.
22.60	Creek, 7 lks. wide; course N.10*W.
29.60	Enter same creek, course N. from SW.
32.00	Hemlock Creek, 12 lks. wide, course N.10*W., from E., at mouth of creek from the S. Thence along W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{2}$ sec. cor., with brass cap marked.
	$\begin{array}{c} \frac{1}{4} \\   \\ S18 \quad   \quad S17 \\   \\ 1927 \end{array}$
	from which, A hemlock; 10 ins. in dia., bears N.75*E., 87 lks. dist., marked $\frac{1}{4}$ S 17 B T A cedar, 10 ins. in dia., bears S.61*W., 86 lks. dist., marked $\frac{1}{4}$ S 18 B T
41.00	Small spur, slopes W. Descend 30 ft. over NW. slope.
47.20	Enter Little River, 22 lks. wide, course SW. from the N.
48.50	Leave Little River, course S. from the NW.
49.17	Stock driveway, bears NW. and SE.
50.70	Little River, course SW. Ascend 180 ft. over S. slope.
55.50	Spur, slopes SW. Descend 70 ft. over NW. slope.
73.70	Junction Creek, 10 lks. wide, course SW. Ascend 127 ft. over SE.slope.
80.00	Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 7, 8, 17 and 18, with brass cap marked.