

Subdivisions, T. 27 S., R. 1 E.

CHAINS

$\frac{1}{4}$ S 7
S 18

1927

from which,

A fir, 16 ins. in dia., bears N.50*E., 34 lks. dist.,
marked $\frac{1}{4}$ S 7 B T

A hemlock, 10 ins. in dia., bears S.49 $\frac{1}{2}$ *E., 42 lks. dist.,
marked $\frac{1}{4}$ S 18 B T

Ascend 647 ft. over broken E. slope.

74.50 Spur, slopes SE.

Descend 42 ft. over SW. slope.

80.12 Intersect the Willamette Meridian, 2.84 chs. N.1*00'E.,
of the cor. of secs. 12 and 13 only, as hereinbefore
described.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. in dia., 14 ins. in
the ground to bedrock, supported in a mound of stone,
with a 3 ft. base, 1 ft. high, for the closing cor.
of secs. 7 and 18, with brass cap marked.

T27S		T27S	
		S 7	— CC
S12		S18	
H1W		R1E	
		1927	

from which,

A fir, 12 ins. in dia., bears N.64*E., 12 lks. dist.,
marked T 27 S R 1 E S 7 C C B T

A fir, 16 ins. in dia., bears S.40*E., 40 lks. dist.,
marked T 27 S R 1 E S 18 C C B T

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, cedar and pine.

Undergrowth, vine maple, rhododendron and chinquapin.