

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 27 S., R. 1 E.

CHAINS

Ascend 205 ft. over broken SE. slope.

62.20 Spur, slopes E.

Descend 132 ft. over NE. slope.

78.30 Creek, 1 lk. wide, course SE.

Ascend 100 ft. over SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 5, 6, 7 and 8, with brass cap marked.

T27SR1E	
S 6	S 5
S 7	S 8
1928	

from which,

A fir, 12 ins. in dia., bears N.42*E., 43 lks. dist., marked T 27 S R 1 E S 5 B T

A fir, 20 ins. in dia., bears S.54*E., 40 lks. dist., marked T 27 S R 1 E S 8 B T

A fir, 46 ins. in dia., bears S.22*W., 12 lks. dist., marked T 27 S R 1 E S 7 B T

A fir, 22 ins. in dia., bears N.32*W., 48 lks. dist., marked T 27 S R 1 E S 6 B T

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, rhododendron, vine maple and chinquapin.

N.89*46'E., on a random line bet. secs. 5 and 8.

40.00 Set temp. 1/2 sec. cor.

80.26 Intersect the N. and S. line, 2 lks. N. of the cor. of secs. 4, 5, 8 and 9.

Thence,

S.89*47'W., on a true line bet. secs. 5 and 8.

Over rolling land, through timber and brush.