

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 27 S., R. 1 E.

CHAINS

West, on a true line bet. secs. 6 and 7.

Over mountainous land, through timber and brush.

Descend 14 ft. over SW. slope.

2.80 Creek, 1 lk. wide, course SE.

Ascend 341 ft. over E. slope.

16.00 Ridge, bears N. and S.

Descend 707 ft. over W. slope.

36.20 Pinnacle Creek, 4 lks. wide, course S.10*W.

Ascend 108 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,

$$\frac{1}{4} \begin{array}{l} S 6 \\ S 7 \end{array}$$

1928

from which,

A yew, 10 ins. in dia., bears S.10*W., 4 lks. dist., marked $\frac{1}{4}$ S 7 B T

A fir, 48 ins. in dia., bears N.20*W., 58 lks. dist., marked $\frac{1}{4}$ S 6 B T

Ascend 147 ft. over SE. slope.

44.30 Small spur, slopes SE.

Descend 203 ft. over SW. slope.

55.50 Draw, course SE., ascend 65 ft. over SE. slope.

60.00 Spur, slopes S., descend 96 ft. over SW. slope.

64.30 Draw, course SE.

66.90 Draw, course SE., ascend 220 ft. over broken E. slope.

78.50 Spring branch, 1 lk. wide, course NE.

79.14 Intersect the Willamette Meridian, 2.87 chs., N.0*04*W., of the cor. of secs. 1 and 12 only, as hereinbefore described.

At intersection:

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 6 and 7, with brass cap marked.